

## Product Brief

### Product Summary

The PC802 is a purpose-designed PHY SoC for 5G NR/LTE small cell disaggregated and integrated RAN architectures, and includes support for industry-leading Open RAN specifications. The SoC interfaces with a layer 2/3 stack via the SCF FAPI interface over PCIe. The PC802 supports seamless interfacing to Radio Units (O-RU) via the O-RAN Open Fronthaul eCPRI interface, or directly to RFICs with a standardised JESD204B high-speed serial interface.

### Key Applications

The PC802 SoC is designed for 5G small cell platforms including:

- ◆ Indoor residential, enterprise and industrial networks
- ◆ Neutral host networks
- ◆ Outdoor networks

The PC802 can be used in:

- ◆ Integrated small cell
- ◆ Split 2 and 6 disaggregated small cells
- ◆ Split 7.2x O-RAN Distributed Unit (DU)
- ◆ Split 7.2x O-RAN Remote Unit (RU)
- ◆ Platforms with variable splits

### Key Features

- ◆ Silicon runs Picocom's 5G NR and LTE PHY (lower and upper) software
- ◆ SCF FAPI interfaces
- ◆ Ceva XC12 5G-optimised 1280-bit vector signal processors
- ◆ RISC-V scalar processor clusters
- ◆ Codecs: LDPC, Turbo and Polar
- ◆ Fourier transforms: FFT, iFFT
- ◆ Equalisers: MMSE/MMSE-IRC/MLD
- ◆ Digital Front End (DFE)
- ◆ O-RAN eCPRI Open Fronthaul
- ◆ IQ compression/decompression
- ◆ Secure on-chip boot capability
- ◆ Debug and device monitoring

### Key Interfaces

- ◆ 4-lane JESD204B radio interface supporting up to 4 RFICs
- ◆ 10/25 Gigabit Ethernet for eCPRI
- ◆ Gen 4 4-lane PCIe interface to NPU
- ◆ LPDDR4 32bit interface (2666/3200MHz)
- ◆ Synchronisation and clock interfaces: IEEE1588v2, GNSS
- ◆ SPI, I2C and GPIO control interfaces

### Key Performance

The PC802 supports 3GPP 5G NR releases 15 and 16, with flexibility for future releases.

The PC802 also supports simultaneous 5G NR/LTE mode, flexible multi-RAT, multi-carrier component configurations and Dynamic Spectrum Sharing (DSS) support.

### 5G NR FR1 Sub-6GHz summary

- ◆ Up to 8 TX/8 RX RF baseband ports
- ◆ 2 UL/4 DL MIMO layers per cell for 2 cells
- ◆ 4 UL/8 DL MIMO layers for 1 cell
- ◆ 100MHz BW per cell
- ◆ Throughput DL: 4Gbps, UL 2Gbps

### 5G NR FR2 mmW summary

- ◆ 2 TX/2 RX RF ports for single cell
- ◆ 2 UL/2 DL MIMO layers
- ◆ 400MHz BW
- ◆ Throughput DL: 3Gbps, UL 3Gbps

### LTE summary

- ◆ Single LTE cell: 4 TX/4 RX antenna ports, 4 UL/4 DL MIMO layers, 20MHz
- ◆ Dual or Tri LTE cells: each cell up to 4 TX/4 RX antenna ports, 2 UL/4 DL MIMO layers, 20MHz
- ◆ Dual mode 5G and 3 LTE cells

### Package summary

- ◆ 25mm x 25mm Thermally Enhanced FCBGA






### Device description

The PC802 device’s function in a small cell use case is, at the highest level, seen as transforming FAPI messages from the L2/3 into IQ samples for the radio, and vice versa. This includes driving the external physical and software interfaces, PHY processing and Digital Front End (DFE) functions.


The PC802 is also optimised to provide upper PHY processing in an O-RAN Alliance O-DU, by transforming the FAPI messages from the L2/3 into frequency domain IQ samples using eCPRI and Open fronthaul messages, which can be transmitted over the Ethernet to O-RU remote radio units.

The high-level PC802 architecture and functional block diagrams for the different use cases are illustrated below.

### Architecture block diagram



### System/functional block diagram for use cases



### Further information

Please contact Picocom [info@picocom.com](mailto:info@picocom.com) for further information.

**Important Information:** Picocom takes great care in publishing materials and makes every effort to provide accurate information. This document outlines a product under development that is subject to change at any time. As a work in progress cannot be totally current, Picocom cannot guarantee their accuracy or completeness. Errors and omissions may occur. Please ensure you have the latest information version available. If in doubt, contact Picocom – [info@picocom.com](mailto:info@picocom.com).